



jalas® HEAVY DUTY 1258

EN ISO 20345:2022 S3, HRO, CI, HI, FO, SC, LG



Learn more

IT'S ALL IN THE NAME

It's all in the name – a tough safety shoe with highest level protection built for tough environments. Specially treated leather with heat resistance para-aramid thread in the seams. The oil and heat-resistant nitrile outer sole means excellent grip and JALAS® Composite Toe Cap, steel puncture protection and double impact protection zones in PORON® XRD® keep feet safe in extreme conditions.

CHARACTERISTICS	FUNCTIONS
• Excellent grip • Perfect fit • Extra comfortable • Excellent shock absorption	• ProNose toe reinforcement • Water repellent • KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit) • Heat-resistant upper • Heat-resistant outsole • Oil-resistant outsole • Anti-static properties • Conforms with IEC 61340-5-1 (ESD) • Bellows tongue • Polstered shaft edge • Double shock absorption zones



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, warm surfaces, environments with risk for outside penetration, oily and greasy environments, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Regular

COLLECTION Heavy Duty

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8217 FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Hook-and-loop

COLOUR Black, Blue

NET WEIGHT, (SIZE 42) 1.4 kg

COMPLIANCE



EN ISO 20345:2022
S3, HRO, CI, HI, FO, SC, LG



ÖNORM Z 1259

TP TC 019:2011

DGUV 112-191

FEATURES



Anti-static properties



Oil-resistant outsole



ProNose toe reinforcement



Nail protection in steel



Heat-resistant outsole



Water repellent



ESD



Composite toecap



Ergothan Shock Absorption System



Heat-resistant upper

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1258-35	6408487505942
36	3	4	5	1258-36	6408487505959
37	4	5	6	1258-37	6408487505966
38	5	5½	6½	1258-38	6408487505973
39	6	6½	7½	1258-39	6408487505980
40	6½	7½	8½	1258-40	6408487505997
41	7	8	9	1258-41	6408487506000
42	8	9	10	1258-42	6408487506017
43	9	9½	11	1258-43	6408487506024
44	10	10½	11½	1258-44	6408487506031
45	10½	11	12½	1258-45	6408487506048
46	11	12	13	1258-46	6408487506055
47	12	13	14	1258-47	6408487506062
48	13	13½	14½	1258-48	6408487506079

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com