



 FIRE 1578 FIRE & RESCUE

EN 15090:2012 F1PA, SRC, T, CI



[Learn more](#)

HEAT RESISTANCE SAFETY BOOT

Safety boot in specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. Nail protection in steel, toecap in aluminium, PU midsole and a rubber outsole.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Ventilating insole
- Pull loops
- Waterproof
- Reflector
- Specially designed details
- Double shock absorption zones



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, warm surfaces, environments with risk for outsole penetration, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Mining, fire fighting, rescue work

SPECIFICATION

TYPE Safety footwear, Boots

CATEGORY Cat. III

NAIL PROTECTION MATERIAL Steel

FITTING Wide

COLLECTION Fire

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide, Drylock membrane

INSOLE FX2 Pro

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

COLOUR Black, Yellow

NET WEIGHT, (SIZE 42) 1.41 kg

COMPLIANCE

C €0598

EAC

EN 15090:2012
F1PA, SRC, T, CI



ÖNORM Z 1259



DGVV 112-191

FEATURES



Anti-static properties



ErgoShock Absorption System



Aluminium toecap



Oil-resistant outsole



Heat-resistant upper



ProNose toe reinforcement



Wide fit



Heat-resistant outsole



Nail protection in steel



Waterproof

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
38	5	5½	6½	1578-38	6408487502583
39	6	6½	7½	1578-39	6408487502590
40	6½	7½	8½	1578-40	6408487502606
41	7	8	9	1578-41	6408487502613
42	8	9	10	1578-42	6408487502620
43	9	9½	11	1578-43	6408487502637
44	10	10½	11½	1578-44	6408487502644
45	10½	11	12½	1578-45	6408487502651
46	11	12	13	1578-46	6408487502668
47	12	13	14	1578-47	6408487502675
48	13	13½	14½	1578-48	6408487502682
49	14	14½	15½	1578-49	6408487503818
50	15	15½	16½	1578-50	6408487503825

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com