

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation	AMBERKLENE FE10
of the mixture	
Registration number	-
Synonyms	None.
Product code	UDS000349AE
Issue date	17-November-2022
Version number	1.0
Revision date	17-November-2022
1.2. Relevant identified uses of t	he substance or mixture and uses advised against
Identified uses	Cleaners - Heavy duty
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Company name	CRC Industries UK Ltd.
Address	Wylds Road
	Castlefield Industrial Estate
	TA6 4DD Bridgwater Somerset
	United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com
Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1
	9240 Zele
	Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com
1.4. Emorgonov tolonhono	Tel: (+44)(0)1278 72 7200 (office bours: 0 17b GMT)

1.4. Emergency telephone number

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Health hazards Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Environmental hazards Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane, Hydrocarbons, C7-C8, cyclics
Hazard pictograms	
Signal word	Danger
Hazard statements	
H222 H229 H315 H336 H411	Extremely flammable aerosol. Pressurized container: May burst if heated. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
recautionary statements	
Prevention	
P102 P210 P211 P251 P261 P271	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist/vapours. Use only outdoors or in a well-ventilated area.
Response	Not assigned.
Storage P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
upplemental label information	According to Regulation (EC) No. 648/2004 on Detergents, as amended; Contains: >30% aliphatic hydrocarbons.
3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No	. Index No.	Notes
Hydrocarbons, C7-C8, cyclics	30 - 60	- 927-033-1	01-2119486992-20	-	
Classification		2;H225, Skin Irrit. 2;H juatic Chronic 2;H41	1315, STOT SE 3;H336, As 1	sp. Tox.	
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	10 - 30	- 921-024-6	01-2119475514-35	-	
Classification		2;H225, Skin Irrit. 2;H juatic Chronic 2;H41	1315, STOT SE 3;H336, As 1	sp. Tox.	
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification	: Press. Gas	;H280			
n-hexane	<3	110-54-3 203-777-6	01-2119480412-44	601-037-00-0	#
Classification			1315, Repr. 2;H361f, STOT 1304, Aquatic Chronic 2;H		

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
4.1. Description of first aid meas	ures
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Not available.
SECTION 8: Exposure c	ontrols/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Li Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	
Methylal (CAS 109-87-5)	STEL	3950 mg/m3	
		1250 ppm	
	TWA	3160 mg/m3	
		1000 ppm	
n-hexane (CAS 110-54-3)	TWA	72 mg/m3	
		20 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.

Recommended monitoring procedures

Derived no effect levels (DNELs)

Components	Value	Assessment factor	Notes
Hydrocarbons, C6-C7, n-alkanes,isoalkane	es,cyclics,< 5% n-hexane (CA	\S -)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation Long-term, Systemic, Oral	699 mg/kg bw/day 608 mg/m3 699 mg/kg bw/day		
Methylal (CAS 109-87-5)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	18.1 mg/kg bw/day 31.5 mg/m3	200 50	Repeated dose toxicity Repeated dose toxicity
Workers			
Components	Value	Assessment factor	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkane	es,cyclics,< 5% n-hexane (CA	\S -)	
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	773 mg/kg bw/day 2035 mg/m3		
Methylal (CAS 109-87-5)			
Long-term, Systemic, Dermal Long-term, Systemic, Inhalation	17.9 mg/kg bw/day 0.31 mg/m3	100 12.5	Repeated dose toxicity Repeated dose toxicity
dicted no effect concentrations (PNECs)			
Components	Value	Assessment factor	Notes
Methylal (CAS 109-87-5)			
Freshwater Secondary poisoning Sediment (freshwater)	14.577 mg/l 7.3 mg/kg 13.135 mg/kg	10 30	Oral

Material name: AMBERKLENE FE10 - Ambersil - europe

Soil	4.654 mg/kg			
STP	10 g/l	1		
8.2. Exposure controls				
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.			
Individual protection measures,	such as personal protective equipme	ent		
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.			
Eye/face protection	Wear safety glasses with side shields	s (or goggles). Use eye protection conforming to EN 166.		
Skin protection				
- Hand protection	time of the glove should be longer that the breakthrough time, gloves should	mical-resistant gloves (standard EN 374). The breakthrough an the total duration of product use. If work lasts longer than I be changed part-way through. Butyl rubber gloves are be recommended by the glove supplier.		
- Other	Wear appropriate chemical resistant of	clothing.		
Respiratory protection	In case of insufficient ventilation, wea organic vapour cartridge and full face	ar suitable respiratory equipment. Chemical respirator with piece. (Filter type AX)		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.		
Hygiene measures		bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work remove contaminants.		
Environmental exposure controls	from ventilation or work process equip requirements of environmental protect	pervisory personnel of all environmental releases. Emissions pment should be checked to ensure they comply with the ction legislation. Fume scrubbers, filters or engineering ent may be necessary to reduce emissions to acceptable		

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Colour	Colourless.
Odour	Solvent.
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	42 °C (107.6 °F)
Flash point	-6.0 °C (21.2 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Explosive limit - lower (%)	0.7 %
Explosive limit – upper (%)	17.6 %
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.77
	0.77 g/cm3 20 °C
Solubility(ies)	0.77 g/cm3 20 °C
Solubility(ies) Solubility (water)	Immiscible with water
• • •	-
Solubility (water) Partition coefficient	Immiscible with water
Solubility (water) Partition coefficient (n-octanol/water)	Immiscible with water Not available.

Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	

Aerosol spray enclosed space

Deflagration density	Not available.
Aerosol spray ignition distance	Not available.
Heat of combustion	Not available.
VOC	731 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

General information

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
Hydrocarbons, C6-C7, n-alkan	es,isoalkanes,cyclics,< 5% n-hexa	ne
<u>Acute</u>		
Dermal		
LD50	Rat	2920 mg/kg bw/day, 24 h
Inhalation		
LC50	Rat	25200 mg/m³, 4 h
Oral		
LD50	Rat	5840 mg/kg bw/day
Hydrocarbons, C7-C8, cyclics		
Acute		
Dermal		
LD50	Rat	2920 mg/kg
Inhalation		
LC50	Rat	23300 mg/m3
Oral		
LD50	Rat	5840 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may	cause temporary irritation.
Respiratory sensitisation	Based on available data, the	classification criteria are not met.
Skin sensitisation	Based on available data, the	classification criteria are not met.

Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Not likely, due to the form of the product.
Mixture versus substance information	Not available.
SECTION 12: Ecological in	nformation

12.1. Toxicity	Toxic to a	quatic life with long lasting effects.	
Components		Species	Test Results
Hydrocarbons, C6-C7, n-alkanes	,isoalkanes,o	cyclics,< 5% n-hexane	
Aquatic			
Acute			
Algae	EC50	Algae	> 30 - < 100 mg/l, 72 h
Crustacea	EC50	Daphnia	3 mg/l, 48 h
Fish	LC50	Fish	11.4 mg/l, 96 h
Hydrocarbons, C7-C8, cyclics			
Acute			
Other	IC50	Pseudokirchnerella subcapitata	10 mg/l, 72 hours
Aquatic			
Acute			
Crustacea	EC50	Daphnia magna	3 mg/l, 48 hours
Fish	LC50	Rainbow trout	3.6 mg/l, 96 hours
Chronic			
Crustacea		Daphnia magna	1 mg/l, 21 days
Fish		Rainbow trout	0.84 mg/l, 28 days
12.2. Persistence and degradability	No data i	s available on the degradability of any ingre	edients in the mixture.
12.3. Bioaccumulative potentia	d.		
Partition coefficient n-octanol/water (log Kow) n-hexane		3.9	
Bioconcentration factor (BCF)	Not availa		
12.4. Mobility in soil	No data a		
12.5. Results of PBT and vPvB assessment		ure does not contain substances assessed I907/2006, Annex XIII.	to be vPvB / PBT according to Regulation
12.6. Other adverse effects	The prode potential. GWP: 0	uct contains volatile organic compounds wh	nich have a photochemical ozone creation

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

ADR UN1950 14.1. UN number 14.2. UN proper shipping **AEROSOLS** name 14.3. Transport hazard class(es) Class 21 Subsidiary risk Not assigned. Hazard No. (ADR) Tunnel restriction code D ADR/RID - Classification 5F code: Not applicable 14.4. Packing group 14.5. Environmental hazards Yes 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user RID UN1950 14.1. UN number AEROSOLS, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk 2.1 Label(s) Not assigned. 14.4. Packing group 14.5. Environmental hazards Yes Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user ADN UN1950 14.1. UN number AEROSOLS, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 21 Subsidiary risk Label(s) 2.1 14.4. Packing group Not assigned. 14.5. Environmental hazards Yes Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user ΙΑΤΑ 14.1. UN number UN1950 14.2. UN proper shipping **AEROSOLS** name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk 14.4. Packing group Not applicable 14.5. Environmental hazards Yes 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user IMDG 14.1. UN number UN1950 AEROSOLS, MARINE POLLUTANT 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk Not applicable 14.4. Packing group 14.5. Environmental hazards Marine pollutant Yes F-D,S-U EmS

Read safety instructions, SDS and emergency procedures before handling.

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Not established.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

n-hexane (CAS 110-54-3)

Other regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

SECTION 16: Other information

List of abbreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road. ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP). CAS: Chemical Abstract Service. Ceiling: Short Term Exposure Limit Ceiling value.
	CEN: European Committee for Standardization. CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures. GWP: Global Warming Potential.
	IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods. MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic.
	REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value.
	TWA: Time Weighted Average. VOC: Volatile organic compounds.
	vPvB: Very persistent and very bioaccumulative. STEL: Short-term Exposure Limit.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
method leading to the	The classification for health and environmental hazards is derived by a combination of calculation
method leading to the classification of mixture Full text of any statements,	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure.
method leading to the classification of mixture Full text of any statements, which are not written out in full under sections 2 to 15	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
method leading to the classification of mixture Full text of any statements, which are not written out in full under sections 2 to 15	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. None.
method leading to the classification of mixture Full text of any statements, which are not written out in full under sections 2 to 15	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.